



NANJING FIRE
TUNA® Sprinklers



NANJING TUNA FIRE PROTECTION CO., LTD.

Nanjing
Tel:+86-25-86986999
Mobile/Whatsapp/Wechat:+86-18352127568
E-mail:export6@tuna.com.cn
Address:No. 599 Zhushan Road,
Jiangning District,Nanjing, Jiangsu,China.
www.tunasprinkler.com



TUNA®
www.tunasprinkler.com

FM&UL Products



Model	Sidewall Sprinkler
Type	NX021
Nominal K-Factor	5.6 (U.S.) / 80 (metric)
Bulb Nominal Dia.	5mm glass bulb
Response	Standard Response
Temp.	57°C, 68°C, 79°C, 93°C
Thread Size	1/2" NPT or 1/2" BSPT
Cert.	FM/UL



Model	Sidewall Sprinkler
Type	NX022
Nominal K-Factor	5.6 (U.S.) / 80 (metric)
Bulb Nominal Dia.	3mm glass bulb
Response	Quick Response
Temp.	57°C, 68°C, 79°C, 93°C
Thread Size	1/2" NPT or 1/2" BSPT
Cert.	FM/UL



Model	Upright Sprinkler
Type	NX023
Nominal K-Factor	5.6 (U.S.) / 80 (metric)
Bulb Nominal Dia.	5mm glass bulb
Response	Standard Response
Temp.	57°C, 68°C, 79°C, 93°C
Thread Size	1/2" NPT or 1/2" BSPT
Cert.	FM/UL



Model	Upright Sprinkler
Type	NX024
Nominal K-Factor	5.6 (U.S.) / 80 (metric)
Bulb Nominal Dia.	3mm glass bulb
Response	Quick Response
Temp.	57°C, 68°C, 79°C, 93°C
Thread Size	1/2" NPT or 1/2" BSPT
Cert.	FM/UL



Model	Pendant Sprinkler
Type	NX025
Nominal K-Factor	5.6 (U.S.) / 80 (metric)
Bulb Nominal Dia.	5mm glass bulb
Response	Standard Response
Temp.	57°C, 68°C, 79°C, 93°C
Thread Size	1/2" NPT or 1/2" BSPT
Cert.	FM/UL



Model	Pendant Sprinkler
Type	NX026
Nominal K-Factor	5.6 (U.S.) / 80 (metric)
Bulb Nominal Dia.	3mm glass bulb
Response	Quick Response
Temp.	57°C, 68°C, 79°C, 93°C
Thread Size	1/2" NPT or 1/2" BSPT
Cert.	FM/UL



Model	Concealed Pendant Sprinkler
Type	NX007
Nominal K-Factor	5.6 (U.S.) / 80 (metric)
Bulb Nominal Dia.	5mm glass bulb
Response	Standard Response
Temp.	57°C, 68°C, 79°C, 93°C (Sprinkler) 57°C, 68°C (Cover Plate)
Thread Size	1/2" NPT or 1/2" BSPT
Cert.	UL



Model	Concealed Pendant Sprinkler
Type	NX008
Nominal K-Factor	5.6 (U.S.) / 80 (metric)
Bulb Nominal Dia.	3mm glass bulb
Response	Quick Response
Temp.	57°C, 68°C, 79°C, 93°C (Sprinkler) 57°C, 68°C (Cover Plate)
Thread Size	1/2" NPT or 1/2" BSPT
Cert.	UL

Water Motor Alarm



Model	Water Motor Alarm
Type	NX010
Alarm Line Inlet	NPT3/4 or Rc3/4*
Drain Outlet	NPT1 or Rc1
Required Accessories	Y-Strainer: 3/4", 20 meshscreen
Working Water Pressure Range	5 to 175 psig / 0.035 to 1.2 MPa (0.35 to 12 bar)
Cert.	UL

Sprinkler Accessories



Model	Concealed Cover Plate
Material	Brass
Surface treatment	White or Chrome Plated or Color Coated In Any Color
Outer dia.	84mm
Apply	1/2" Concealed sprinklers



Model	Adjusted two-piece escutcheon
Material	SPCC
Surface treatment	Chrome Plated/White Plated
Outer dia.	75mm
Inner dia.	47mm
Apply	1/2" sprinklers



Model	One-piece escutcheon
Material	SPCC
Outer dia.	72mm
Height	13mm
Apply	1/2" sprinklers



Model	Sprinkler Wrench
Material	Carbon Steel
Surface treatment	SGCC
Length	200mm
Apply	1/2" sprinklers



Model	Sprinkler Head Guard
Material	Steel iron
Surface treatment	Red Coated
Apply	1/2" sprinklers



Model	Fire Sprinkler Cabinet
Material	Steel iron
Surface treatment	Red Coated
Optional	3/6/12/24/36 heads
Apply	1/2" , 3/4" sprinklers